



NOTE:
SHALLOW PIT DEPTH REQUIRES SAFETY DEVICE IN ACCORDANCE WITH ASME A17.1 CODE. SAFETY DEVICE IS PROVIDED BY CANTON.

AN AREA OF 5.49 SQUARE FEET (NOT LESS THAN 24 INCHES ON ANY SIDE) IS TO BE LOCATED ON THE CAR TOP WHERE 43 INCHES MINIMUM OF VERTICAL CLEARANCE EXIST WITH THE CAR AT ITS MAXIMUM LIMIT OF TRAVEL. THIS AREA IS TO BE INDICATED ON THE CAR TOP AS REQUIRED BY ASME/ANSI A17.1.

THE RAILS FOR THIS JOB ARE APPROXIMATELY 16'-0" LONG. MAKE SURE THAT THIS LENGTH COMPONENT CAN BE MOVED THROUGH THE JOB SITE INTO THE HOISTWAY.

Plan View @ "PH"
SCALE : NONE
(DEPICTING FEATURES AT VARIOUS LEVELS)

DATE	BY	CHKD	DESCRIPTION
11-03-17	ewd		ORIGINAL

PROJECT	
FRONT AND SIDE 1400# L.U./L.A.	
CONTRACT No.	SHEET No.
	2 OF 4